



THE EXHIBITORS'™
**HAND
BOOK**
MODULAR DISPLAY SOLUTIONS

GRAPHIC

ARTWORK GUIDELINES

ARTWORK GUIDELINES

ACCEPTABLE FILE FORMATS

High quality PDF (preferred)
Illustrator CC or below
Photoshop CC or below
InDesign CC or below (not preferred)

High quality, editable PDF's, Illustrator and Photoshop files are preferred, as they are more suitable for large format printing. Art time will be charged if files need to be fixed or altered to meet guidelines. When sending files, please be sure to include all support art (fonts, linked images, etc.).

Please note that Illustrator special effects such as glows, transparencies or drop shadows are not recommended. These effects sometimes have unpredictable results when printing. Photoshop is preferred when using such special effects.

FONT SPECIFICATIONS

Fonts must be converted to outlines. If fonts are not created to outlines, please provide Macintosh or TrueType fonts. If changes need to be made in the file, please provide the fonts and a version of the file with editable type.

COLOR SPECIFICATIONS

Please provide all vector files (Illustrator & InDesign) in CMYK format. Please supply all raster artwork (Photoshop files, jpgs, tiffs) in RGB format for the most accurate color output. Please provide a hard copy proof of the files being printed for color accuracy and a PDF layout for file layout accuracy.

If Pantone colors need to be matched please specify on purchase order or hard copy reference. All critical Pantone colors need to be called out in the file as solid coated swatches. If multiple Pantone swatches are used in the file, all will be matched to solid coated unless otherwise specified.

If color matching to existing graphics, we will need those back to review. Please contact your sales representative for a case number.

FTP SITE GUIDELINES

We provide an FTP site to upload files quickly and at no additional cost. The site can be accessed through a web browser or an FTP software such as FETCH. Please read below for detailed instructions.

1. Place all art files in a folder. Please name the folder by client name and purchase order number.
2. Compress files using software such as WinZip or Stuffit. All compressed files must be under 500MB.
3. Access the FTP by web browser or FTP software.

WEB BROWSER:

Address:
<http://www.handbookart.com>
no user ID
no password
choose the anonymous login option

FTP SOFTWARE:

Address:
<ftp.handbookart.com>
no user ID
no password

4. When your upload is complete, please place the order with your sales representative and include any critical file information.

Please feel free to submit catalogs, brochures, printed proofs, etc. to use as a color reference. Please provide a layered file for Photoshop files if color matching is required. Art time may be charged to correct flattened Photoshop files.

We guarantee color matching on all hard copy proofs, specified Pantone colors and client-supplied hard copy proofs. Orders without indication of Pantone colors, supplied proofs or requested hard copy proofs are NOT guaranteed for color.

RESOLUTION

All raster files (either print files or linked files) must be at 100-120 pixels per inch at 100%.

VINYL CUT GRAPHICS

Artwork must be set up as a vector file with fonts created to outlines for all cut vinyl. Please specify every color number for solid color vinyl or PMS color for adhesive back and cut vinyl.

SUBMITTING ARTWORK FILES

Files are accepted via Email (up to 10MB), FTP site, DVD and CD or File Transfer site such as WeTransfer or Hightail.

Files can be uploaded to:
www.handbookart.com

Please reference the FTP site guidelines for more information.

MURALS AND POPUP GRAPHICS

Popup mural files must be built as one file. Please note where panel breaks are located and try to minimize the amount of type that crosses over the panel breaks.



BLEED SPECIFICATIONS

All graphics produced require specific bleeds. Below is a general outline for the required bleeds.

- **MURAL POPUP FILES:**
1/2" bleed around the perimeter.
- **COLLAPSIBLE FABRIC DISPLAYS, TENSION FABRIC BACKWALLS AND EXTRUSION FRAME BANNERS AND BACKWALLS:**
2" bleed around the perimeter. Please keep all logos, type, and critical information at least 2" in from the visual edge of the graphic.
- **FABRIC STRUCTURES:**
5" bleed around the perimeter.
- **BANNER STAND GRAPHICS:**
Each product has specific bleed requirements. Please refer to the graphic template for specific information. Different printing processes may require different bleeds. All banner stand graphics printed on Resilience will require an extra 1" bleed around the perimeter.
- **CUSTOM DYE SUB FLAG GRAPHICS:**
2" bleed left & right sides,
4" bleed at the top & bottom.
- **ORBITAL EXPRESS™ TRUSS GRAPHICS - UV:**
1/2" bleed around the perimeter.
- **ORBITAL EXPRESS™ TRUSS GRAPHICS - DYE SUB:**
2" bleed around the perimeter.
- **CUSTOM CONTOUR CUT UV GRAPHICS:**
1/2" bleed around the perimeter.
- **CUSTOM DYE SUB GRAPHICS:**
2" bleed around the perimeter.
- **CUSTOM DYE SUB GRAPHICS EXCEEDING 160":**
5" bleed around the perimeter.



TEMPLATES FOR PRODUCTS
ARE AVAILABLE ONLINE AT

WWW.EXHIBITORS-HANDBOOK.COM